

WHAT IS CLAIMED IS:

- 2000000-5222000
1. An anchoring device for joining three boards, which comprises:
- (a) a substantially flat horizontal top element having a top view configuration which includes two sides and has a first predetermined width as measured side to side, said first predetermined width being measured at a maximum width between said two sides, said top element having an imaginary center line;
  - (b) at least one substantially vertical support member attached to the underside of said top element along said imaginary center line of said top element and extending downwardly therefrom for a predetermined length, said substantially vertical support member having two

sides and a second predetermined width as measured side to side at its maximum width; and,

(c) a substantially flat horizontal bottom element having a flat bottom view configuration which includes two sides and has a third predetermined width as measured side to side at its maximum width;

wherein said first predetermined width is greater than both said second predetermined width and third predetermined width, and wherein said third predetermined width is greater than said second predetermined width, and said anchoring device is adapted to maintain said top element in a predetermined position during use for joinder of two adjacent boards which have been pre-cut with receiving slots, and to position said bottom

100225-010300

element upon a support board which said two adjacent boards rest for attachment of said anchoring device to said support board for anchoring and support of said two adjacent boards.

2. The anchoring device of claim 1 wherein said bottom element has a generally trapezoidal shape with its greatest width at a trapezoidal base.

3. The anchoring device of claim 1 wherein said vertical support member has a plurality of recesses with support columns located therebetween.

4. The anchoring device of claim 1 wherein said device is made of molded plastic material capable

10037325-010302

of having a metal fastener driven through.

5. A decking system which comprises:

I. a plurality of decking boards, each decking board having a top, a bottom, two sides, and two ends, and at least one groove located along one of said sides, said groove adapted to receive an anchoring device; and,

II. an anchoring device which comprises:

(a) a substantially flat horizontal top element having a top view configuration which includes two sides said and has a first predetermined width as measured side to side, said first predetermined width being measured a maximum width between said sides, said top element having an imaginary center line;

(b) at least one substantially vertical

10037325-010302

support member attached to the underside of said top element along said imaginary center line of said top element and extending downwardly therefrom for a predetermined length, said substantially vertical support member having two sides and a second predetermined width as measured side to side at its maximum width; and,

(c) a substantially flat horizontal bottom element having a flat bottom view configuration which includes two sides and has a third predetermined width as measured side to side at its maximum width;

wherein said first predetermined width is greater than both said second predetermined width and third predetermined width, and wherein said third predetermined width is greater than said

second predetermined width, and said anchoring device is adapted to maintain said top element in a predetermined position during use for joinder of two adjacent boards which have been pre-cut with receiving slots, and to position said bottom element upon a support board which said two adjacent boards rest for attachment of said anchoring device to said support board for anchoring and support of said two adjacent boards.

6. The decking system of claim 5 wherein said bottom element has a generally trapezoidal shape with its greatest width at a trapezoidal base.

7. The decking system of claim 5 wherein

1003226 040300

said vertical support member of said anchoring device has a plurality of recesses with support columns located therebetween.

8. The decking system of claim 5 wherein said device is made of molded plastic material capable of having a metal fastener driven through.

9. The decking system of claim 5 wherein said groove establishes an upper half of said board above said groove and a lower half of said board below said groove, wherein said upper half has a greater width than said lower half.

10. The decking system of claim 5 wherein said plurality of decking boards are made of

20250707 09:10:30

materials selected from the group consisting of synthetic polymers, at least partially foamed synthetic polymer, wood, wood composite, and combinations thereof.

11. An anchoring device for joining three boards, which comprises:

(a) a substantially flat horizontal top element having a top view configuration which includes two parallel sides and has a first predetermined width as measured side to side, said top element having an imaginary center line;

(b) at least one substantially vertical support member attached to the underside of said top element along said imaginary center line of said top element and extending downwardly therefrom for a predetermined length, said

2025-07-01 14:00:00



substantially vertical support member having two parallel sides and a second predetermined width as measured side to side; and,

(c) a substantially flat horizontal bottom element having a flat bottom view configuration which includes two parallel sides and has a third predetermined width as measured side to side;

wherein said first predetermined width is greater than both said second predetermined width and third predetermined width, and wherein said third predetermined width is greater than said second predetermined width, and said anchoring device is adapted to maintain said top element in a predetermined position during use for joinder of two adjacent boards which have been pre-cut with receiving slots, and to position said bottom

10037325-010302

element upon a support board which said two adjacent boards rest for attachment of said anchoring device to said support board for anchoring and support of said two adjacent boards.

12. The anchoring device of claim 11 wherein said bottom element has a generally trapezoidal shape with its greatest width at a trapezoidal base.

13. The anchoring device of claim 11 wherein said vertical support member has a plurality of recesses with support columns located therebetween.

14. The anchoring device of claim 11 wherein said device is made of molded plastic material capable

1003325-010300

of having a metal fastener driven through.

15. A decking system which comprises:

I. a plurality of decking boards, each decking board having a top, a bottom, two sides, and two ends, and at least one groove located along one of said sides, said groove adapted to receive an anchoring device; and,

II. an anchoring device which comprises:

(a) a substantially flat horizontal top element having a top view configuration which includes two parallel sides and has a first predetermined width as measured side to side, said top element having an imaginary center line;

(b) at least one substantially vertical support member attached to the underside of said top element along said imaginary center line of

100325 040300  
200000 000000



of two adjacent boards which have been pre-cut with receiving slots, and to position said bottom element upon a support board which said two adjacent boards rest for attachment of said anchoring device to said support board for anchoring and support of said two adjacent boards.

16. The decking system of claim 15 wherein said bottom element has a generally trapezoidal shape with its greatest width at a trapezoidal base.

17. The decking system of claim 15 wherein said vertical support member of said anchoring device has a plurality of recesses with support columns located therebetween.

10037325-010302

18. The decking system of claim 15 wherein said device is made of molded plastic material capable of having a metal fastener driven through.

19. The decking system of claim 15 wherein said groove establishes an upper half of said board above said groove and a lower half of said board below said groove, wherein said upper half has a greater width than said lower half.

20. The decking system of claim 15 wherein said plurality of decking boards are made of materials selected from the group consisting of synthetic polymers, at least partially foamed synthetic polymer, wood, wood composite, and combinations thereof.

10037325-010302